460BMAZR-N2E

BACnet MS/TP devices to Microsoft Azure

FEATURES

- Fully configurable BACnet MS/TP Manager
- BACnet MS/TP supports device, binary I/O/V, analog I/O/V, multi-state I/O/V, and character string value object types
- Supports JSON formatted MQTT payload
- Allows factory floor based devices to move its data to IT
- Effortless Browser
 Based Configuration,
 no programming
 software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect BACnet MS/TP Devices to Microsoft Azure

The 460BMAZR moves data between up to 32 BACnet MS/TP devices and Microsoft Azure. Connect your BACnet MS/TP devices to the Microsoft Azure cloud based platform. Allowing you to easily log data and leverage in populating dashboards.

Best of all, the product comes with 5-year warranty.

How Do I Use the 460BMAZR-N2E in My Application?

Analog and binary BACnet data value can be sent as Device-To-Cloud messages or received as Cloud-To-Device messages.

SSL transport layer security protects the data moving from your operations network to the cloud.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



A Solution, A Philosophy, the RTA Way. We understand the long hours spent on a factory floor and the pressure to keep a line running and product flowing. That's how Real Time Automation came to be. You want easy-to-use solutions where the hardest part is to open the box. You need customer support second to none. If you get all that and a fun customer experience all the better. Thirty years later, our mission remains the same: To move your data where you need it, when you need it, and how you need it.

Specification

Operation Mode	BACnet MS/TP Manager Initiator		
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value		
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A		
Maximum Connections	32		
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes		
Scan Line Support	Up to 128 Objects		
AZURE CLIENT FEATURES			
Operation Mode	Microsoft Azure		
Max Broker Connections	1 Azure		
Max Data Points Per Connection	250 Read Topics, 1 Write Topic		
Security	SSL cloud access		
Supported Data Formats	JSON		
Data Payload	Topic Name and Value		
INCLUDED WITH GATEWAY			
3' power cable with flying leads	5-year hardware warranty		
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life		
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff		
Manual			

Status and Counters Status and Counters Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a	ELECTRICAL / ENVIRONMENTAL		
Operating Temperature -40 C to 85 C Certification RoHS-Compliant, UL, CUL, CE Approvals, Class 1 Div 2 ENCLOSURE / HARDWARE Size 5.40" x 3.83" x 1.19" Weight 7.6 oz Enclosure Type Anodized Aluminum Mounting Din rail or panel mount LEDs Power LED & 2 general purpose LEDs on side GATEWAY FEATURES & FUNCTIONS Set <, <, >, >, =, =, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offe customizations for unique applications.	DC Input Voltage	12-24 VDC	
Certification RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2 ENCLOSURE / HARDWARE Size 5.40" x 3.83" x 1.19" Weight 7.6 oz Enclosure Type Anodized Aluminum Mounting Din rail or panel mount LEDs Power LED & 2 general purpose LEDs on side GATEWAY FEATURES & FUNCTIONS Set <, <=, >, =, ==,!=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications. Allows users to see and log start up sequences,	Maximum Baud Rate	115K baud	□ (• • •
ENCLOSURE / HARDWARE Size 5.40" x 3.83" x 1.19" Weight 7.6 oz Enclosure Type Anodized Aluminum Mounting Din rail or panel mount LEDs Power LED & 2 general purpose LEDs on side GATEWAY FEATURES & FUNCTIONS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications. Allows users to see and log start up sequences,	Operating Temperature	-40 C to 85 C	
Size 5.40" x 3.83" x 1.19" Weight 7.6 oz Enclosure Type Anodized Aluminum Mounting Din rail or panel mount LEDs Power LED & 2 general purpose LEDs on side GATEWAY FEATURES & FUNCTIONS Alarming Set <, <=, >, >=, ==,!=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list Www.rtautomation.com/products. We also offer customizations for unique applications.	Certification		3.83
Size S.40 X 3.83 X 1.19 Weight 7.6 oz Anodized Aluminum Mounting LEDs Power LED & 2 general purpose LEDs on side GATEWAY FEATURES & FUNCTIONS Set <, <=, >, >=, ==,!=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications. Allows users to see and log start up sequences,	ENCLOSURE / HARDWARE		0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Weight 7.6 oz Enclosure Type Anodized Aluminum Mounting Din rail or panel mount LEDs Power LED & 2 general purpose LEDs on side GATEWAY FEATURES & FUNCTIONS Set <, <=, >, >=, ==,!=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications. Allows users to see and log start up sequences,	Size	5.40" x 3.83" x 1.19"	
Mounting Din rail or panel mount Power LED & 2 general purpose LEDs on side GATEWAY FEATURES & FUNCTIONS Set <, <=, >, >=, ==,!=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications. Allows users to see and log start up sequences,	Weight	7.6 oz	
Power LED & 2 general purpose LEDs on side GATEWAY FEATURES & FUNCTIONS Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. Allows users to see and log start up sequences, Allows users to see and log start up sequences,	Enclosure Type	Anodized Aluminum	
Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profix give us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications.	Mounting	Din rail or panel mount	
Alarming any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications. Allows users to see and log start up sequences,	LEDs	Power LED & 2 general purpose LEDs on side	
Alarming any data moving through the gateway. If alarm rule is triggered an email notification can be sent. You can configure up to 9 different users access to diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications. Allows users to see and log start up sequences,	GATEWAY FEATURES & FUNCTIONS		
diagnostic and configuration screens. Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profice us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications. Allows users to see and log start up sequences,	Alarming	any data moving through the gateway. If alarm rule	
Translation Table translation. Scaling and other data format changes can occur in the gateway. Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device. NOT EXACTLY WHAT YOU WERE LOOKING FOR Real Time Automation offers a full line of gateway profers us a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications. Allows users to see and log start up sequences,	Gateway Security		
Status and Counters Real Time Automation offers a full line of gateway program as a call at 1-800-249-1612. Or, check out a list www.rtautomation.com/products. We also offer customizations for unique applications. Allows users to see and log start up sequences,	Translation Table	translation. Scaling and other data format changes	
Disanctic Logging Dage	Status and Counters	messages are accessible within the gateway's diagnostics page. They can also be delivered to a	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at www.rtautomation.com/products . We also offer customizations for unique applications.
	Diagnostic Logging Page		

CATALOG #	DESCRIPTION
460BMAZR-N2E	Connect up to 32 BACnet MS/TP devices to Microsoft Azure









