

CONTACT US! 1-800-249-1612 rtautomation.com

460BMWI-NNA1

Connect a Web Interface to BACnet MS/TP Subordinates

FEATURES

- Fully configurable BACnet MS/TP Manager
- BACnet MS/TP supports device, binary I/O/V, analog I/O/V, multi-state I/O/V, and character string value object types
- Get PLC data table entries encoded in either JSON or XML
- Bidirectional data transfer supports both HTTP GET and POST
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Deliver Data from Your BACnet MS/TP subordinate Devices to a Web Interface

The 460BMWI moves data between up to 32 BACnet MS/TP Subordinate devices and a web server or a web client. Use that data to easily build an Excel log, a dashboard, archive data, or create a sophisticated alarm system. Best of all, the product comes with a 5-year warranty.

How Do I Use the 460BMWI-NNA1 in My Application?

First, you configure the 460BMWI using the browser-based configuration pages. You'll identify the data set to read / write on BACnet. Once that's complete, you'll map, name, and group the data to be presented as XML or JSON files. Your application can issue standard HTTP GET or POST instructions to move data into your application. Up to 1000 data points can be moved in each direction.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.


When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.



MS/TP Subordinates

460BMWI-NNA1

Web Interface



Specification

BACNET MS/TP MANAGER FEATURES				
Operation Mode	BACnet MS/TP Manager Initiator			
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value			
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A			
Maximum Connections	32			
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes			
Scan Line Support	Up to 128 Objects			
WEB INTERFACE FEATURES				
Max Web Interface Connections	One (gateway acting as client) / Unlimited (gateway acting as server)			
Encodings	JSON and XML			
Proxy Support	HTTP, SOCKS5 for Client			
Maximum Number of Input Data Points	1000 JSON Fields or 1000 XML Tags			
Maximum Number of Output Data Points	1000 JSON Fields or 1000 XML Tags			
HTTP Services	Client: POST only; Server: GET and POST			
INCLUDED WITH GATEWAY				
3' power cable with flying leads	5-year hardware warranty			
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life			
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff			
Manual				

ELECTRICAL / ENVIRONMENTAL				
DC Input Voltage	12-24 VDC			
Maximum Baud Rate	115K baud	DIN Rail N	rount	
Operating Temperature	-40 C to 85 C		3.88	
Certification	RoHS-Compliant, UL, CUL, CE Approvals	1		
ENCLOSURE / HARDWARE				
Size	3.88" x 2.57" x 1.06"			
Weight	5.5 oz			
Enclosure Type	Anodized Aluminum	2.57		
Mounting	Din rail or panel mount			
LEDs	Power LED & 2 general purpose LEDs on side		Note: All dimensions	
GATEWAY FEATURES & FUNCTIONS			are in Inches	
Alarming	Set <, <=, >, >=, ==, !=, and change-of-state rules on any data moving through the gateway. If alarm rule is triggered an email notification can be sent.	·	69999 69	
Gateway Security	You can configure up to 9 different users access to diagnostic and configuration screens.	1.06		
Translation Table	Allows for data manipulation during protocol translation. Scaling and other data format changes can occur in the gateway.			
Status and Counters	Protocol specific status, counters, and error messages are accessible within the gateway's diagnostics page. They can also be delivered to a connected device.	NOT EXACTLY WHAT YOU WERE LOOKING FOR? Real Time Automation offers a full line of gateway products. Give us a call at 1-800-249-1612. Or, check out a listing at <u>www.rtautomation.com/products</u> . We also offer customizations for unique applications.		
Diagnostic Logging Page	Allows users to see and log start up sequences, protocol specific messages & error messages.			

CATALOG # 460BMWI-NNA1	DESCRIPTION Connects up to 32 interface	Connects up to 32 BACnet MS/TP Subordinates devices to a web				
Ë		Coro	MARRANTTY MARRANTTY	i		

READY TO SHIP

Real Time Automation, Inc.

ALWAYS IN STOCK

solutions@rtautomation.com

5-YEAR WARRANTY

ENGINERD SUPPORT

EMPLOYEE OWNED