

CONTACT US! 1-800-249-1612 rtautomation.com

Real Time Automation Gateways

460MMBM-N34

Modbus RTU Servers to BACnet MS/TP

FEATURES

- Fully configurable Modbus RTU Client
- Connects up to 32 Modbus RTU Servers
- Fully configurable BACnet MS/TP Manager
- BACnet MS/TP supports device, binary I/O/V, analog I/O/V, multi-state I/O/V, and character string value object types
- Effortless Browser Based Configuration, no programming software is required
- Simple data translation allows you to manipulate data as it passes between protocols
- 5-Year Hardware Warranty

Connect Modbus RTU Servers to BACnet MS/TP Devices

The 460MMBM moves data between a network of up to 32 Modbus RTU Servers and up to 32 BACnet MS/TP devices. With the 460MMBM, you're mapping Modbus coil and register data directly to BACnet MS/TP as binary and analog values.

How Do I Use the 460MMBM-N34 in My Application?

Modbus register data is mapped to BACnet analog objects and Modbus coil data is mapped to Binary objects. The only additional piece required for BACnet is adding metadata which is nothing more than an ASCII description of each object. It really is that simple.

Why Use Real Time Automation as a Gateway Supplier?

While there are certainly other companies offering protocol gateways, there is no one who provides the level of support and service that you receive from RTA.

When you call, a live person answers the phone. When you talk with sales, you will get honest answers and recommendations. When you get support, it is from an engineer who had a hand in the product's development, and support doesn't require a ticket or 24-hour wait.




RTU Servers



460MMBM-N34



MS/TP Subordinates



Specification

MODBUS RTU CLIENT FEATURES	
Operation Mode	Modbus RTU Client
Function Codes Supported	1,2,3,4,5,6, 15 & 16
Swapping	Byte and Word Swapping
Maximum Modbus RTU Server Devices	32
Number Read/Write Scan Lines per RTU Server Device	200 Total - 100 reads & 100 writes
Scan Line Support	Up to 125 Registers or 512 Coils
BACNET MS/TP MANAGER FEATURES	
Operation Mode	BACnet MS/TP Manager Initiator
Supported Object Types	Device, BI/BO/BV, AI/AO/AV, MI/MO/MV, Character String Value
Supported Service Codes	Read Property-A, Read Property Multiple-A, Write Property-A, Write Property Multiple-A, Device Dynamic Binding-A
Maximum Connections	32
Number Read/Write Scan Lines per Device	200 Total - 100 reads & 100 writes
Scan Line Support	Up to 128 Objects
INCLUDED WITH GATEWAY	
3' power cable with flying leads	5-year hardware warranty
IPSetup software – automatically locates RTA gateway on the network	Unlimited firmware feature upgrades for life
CAT5 crossover cable for direct connection to PC during programming	Complete, unlimited access to our industry leading support staff
Manual	

ELECTRICAL / ENVIRONMENTA	NL			
DC Input Voltage	8 VDC @ 230mA to 28 VDC @ 80 mA			
Maximum Baud Rate	115K baud	LEO		
Operating Temperature	-40 C to 85 C			
Certification	RoHS-Compliant, UL, CUL, CE Approvals, Class I Div 2	ζ		Port 1
ENCLOSURE / HARDWARE		3.25		
Size	4.2" x 3.25" x 1"	3.25		
Weight	7 oz			Post 0 000000
Enclosure Type	Anodized Aluminum			Porto
Mounting	Din rail or panel mount			
LEDs	Ethernet link/data LED, Ethernet speed LED, 1.00	1.00	4.19	1.00
LLDS	power LED, & 2 general purpose LEDs on side			
GATEWAY FEATURES & FUNC	TIONS	Din Rail		
	Set <, <=, >, >=, ==, !=, and change-of-state rules on			-
Alarming	any data moving through the gateway. If alarm rule			
	is triggered an email notification can be sent.	Panel Mount		
Catalan Caralita	You can configure up to 9 different users access to			
Gateway Security	diagnostic and configuration screens.			
	Allows for data manipulation during protocol			
Translation Table	translation. Scaling and other data format changes			
	can occur in the gateway.			
	Protocol specific status, counters, and error	NOT EXACTLY WH	AT YOU WERE I	OOKING FOR?
Status and Counters	messages are accessible within the gateway's	Real Time Automation	offers a full line o	f gateway products.
	diagnostics page. They can also be delivered to a	Give us a call at 1-800	-249-1612. Or, cl	neck out a listing at
	connected device.	www.rtautomatic	on.com/products.	We also offer
	connected device.	customizatio	ons for unique app	lications.
Diagnostic Logging Page	Allows users to see and log start up sequences,			
2.20.0000 2000116 1 480	protocol specific messages & error messages.			

CATALOG #	DESCRIPTION
460MMBM-N34	Connects up to 32 Modbus RTU Servers with as many as 32 BACnet MS/TP Subordinates









EXPERT SUPPORT





EMPLOYEE OWNED

READY TO SHIP

MADE IN THE USA

solutions@rtautomation.com

1-800-249-1612

Real Time Automation, Inc.